

kontrol

Evinizdeki sıcaklığın kontrolü sizde

Clai® kontrol cihazları; radyatör ve klima termostatlarından TV, su panellerine, perde kumandalarından sahne düğmelerine ve genişletilmiş röle modüllerine kadar evinizdeki tüm sistemleri tek noktada birleştirir.

clai



Smart Radiator Thermostat



ZAI-SCU-RAD

Type	Smart Radiator Thermostat
Input Voltage	BAT. AA Alkaline Type*2
Connection	M30 x 1.5mm
Temperature Range	5°C~60°C
Temperature Display	0°C~60°C
Working Temperature	-10°C~40°C

Smart Thermostat Panel



ZAI-SCU-TP

Type	Smart Thermostat Panel
Input Voltage	100-240VAC 50/60Hz
Work. Consumption	<1.5W
Temp. Accuracy	±1°C
Display Range	5°C~99°C
Dimensions	88*88*26mm

Smart Knob Thermostat Panel



ZAI-SCU-KTP

Type	Smart Knob Thermostat Panel
Input Voltage	100-240VAC 50/60Hz
Output Current	3A-16A
Temp. Accuracy	±1°C
Temp. Range	5°C~99°C
Dimensions	88*88*26mm

Smart IR & RF Control



ZAI-SCU-IR+RF

Type	Smart Remote Controller
Input Voltage	USB
Control Type	IR / RF
IR Angle	360°
Standby Power	0.5W
IR Frequency	38Khz

Smart ZigBee Gateway



ZAI-SCU-ZG

Type	Smart ZigBee Gateway
Input Voltage	USB 5V 2A
Connection	Wi-Fi / ZigBee / BLE
Working Humidity	10%~90%RH
Working Temperature	-10°C~45°C
Dimensions	60x60x14mm

Smart Knob Scene Control



ZAI-SCU-SC

Type	Smart Knob Scene Control
Input Voltage	BAT. CR2032*1
Connection	ZigBee 3.0
Scene Control	Single/Double/Long/Rotate
Working Temperature	-10°C~45°C
Dimensions	45x45x19mm





Smart Roller Blinds Control



ZAI-SCU-RB

Type	Smart Roller Blinds Control
Input Voltage	USB 5V 2A
Torque	0.55nm
Speed Range	20-50rpm
Rated Current	1.2A
Noise Level	<33dB

Smart Curtain Robot



ZAI-SCU-CR

Type	Smart Curtain Robot
Input Voltage	USB TypeC / Li-Ion
Work. Consumption	4W
Speed	10s/mt.
Pushing Force	8-10Kg
Dimensions	118*87*62mm

6Ch. Relay Controller



ZAI-SCU-RC6

Type	6Ch Relay Controller
Input Voltage	110-240VAC 50/60Hz
Max. Current	16A/Ch
Power Rating	3680W
Standby Power	<1W
Cable Connection	Rs485

Smart Irrigation

1,8
mt

ZAI-SCU-IRRI

Type	Smart Irrigation System
Input Voltage	BAT. AA Type*4
Water Pressure	1~8Kg
Working Flow	500-1700L/h
Connection	1/2" - 3/4"
Working Temperature	0°C~60°C


Smart Valve Control



ZAI-SCU-VV

Type	Smart Valve Control
Input Voltage	100-240VAC 50/60Hz
Valve Pressure	1.6MPA
Torque	30-60kg.cm
Connection	1/2" - 3/4"
Rated Power	1.2W

16Ch. Relay Controller



ZAI-SCU-RC16

Type	16Ch Relay Controller
Input Voltage	110-240VAC 50/60Hz
Max. Current	16A/Ch*12 - 50A/Ch*4
Power Rating	3680W*12 / 11500W*4
Standby Power	<3W
Cable Connection	Rs485

