

sensör

DAVETSİZ misafirler İÇİN

Clai® sensör ürünlerimiz, kablosuz kurulum kolaylığı ve uzun pil ömrüyle evinizi anlık izlemeye alır; hareket sensörleri otomatik aydınlatma ve ısı ayarlarını devreye sokar, kapı/pencere sensörleri izinsiz girişleri anında bildirir, duman ve gaz sensörleri tehlikeyi hızla algılar, su kaçak sensörleri olası hasarı engellemeye yardımcı olur ve nem-sıcaklık sensörleri iklim kontrolünü optimize ederek enerji tasarrufu sağlar. Tüm veriler, mobil uygulama üzerinden merkezi olarak izlenip yönetilerek hem güvenliği hem konforu en üst düzeye taşır.

clai



Smart Door / Window Sensor



ZAI-SS-DW

Type	Smart Door/Window Sensor
Input Voltage	BAT. CR123*1
Detection Type	Open / Close
Working Current	55mA
Standby Current	45uA
Working Temperature	-10°C~50°C

Smart Vibration Sensor



ZAI-SS-V

Type	Smart Vibration Sensor
Input Voltage	BAT. AAA Type*2
Working Humidity	<95%
Alarm Current	<20mA
Standby Current	10uA
Working Temperature	-10°C~50°C

Smart Water Leak Sensor



ZAI-SS-WLC

Type	Smart Water Leak Sensor
Input Voltage	BAT. LR03*2
Working Humidity	<95%
Detection Type	Alarm
Standby Current	25uA
Working Temperature	-10°C~55°C

Smart Water Leak Sensor



ZAI-SS-WL

Type	Smart Water Leak Sensor
Input Voltage	BAT. CR2032*1
Working Humidity	<95%
Detection Type	Alarm
Standby Current	25uA
Working Temperature	-10°C~55°C

Smart Temp. / RH Sensor



ZAI-SS-TH

Type	Smart Temp/RH Sensor
Input Voltage	BAT. LR03*2
Working Humidity	10%~95%
Low Power	<2.7VDC
Standby Current	<30uA
Working Temperature	-10°C~55°C

Smart Temp./RH/IR Sensor



ZAI-SS-THS

Type	Smart Temp/RH/IR Sensor
Input Voltage	USB
Working Humidity	10%~95%
Control	Infrared Remote
Standby Power	0.5W
Working Temperature	-10°C~55°C





Smart Motion Sensor



ZAI-SS-PIR

Type	Smart Motion Sensor
Input Voltage	USB / BAT. LR03*2
Detection Range	0-6mt.
Detection Angle	120°
Standby Current	75uA
Working Temperature	-10°C~50°C

Smart Motion Sensor



ZAI-SS-PIR-MINI

Type	Smart Motion Sensor
Input Voltage	BAT. CR123A*1
Detection Range	0-7mt.
Detection Angle	110°
Standby Current	20uA
Working Temperature	0°C~40°C

Smart Human Presence Sensor



ZAI-SS-HPS

Type	Smart Human Presence Sensor
Input Voltage	USB
Detection Range	0-6mt.
Detection Angle	90°
Luminance	0~3000Lux
Working Temperature	-10°C~55°C

Smart Smoke Sensor



ZAI-SS-SM

Type	Smart Smoke Sensor
Input Voltage	BAT. LR03*1
Detection Range	0-20mt.
Detection Angle	110°
Alarm Current	<160mA
Alarm Volume	80db/1mt.

Smart Gas Sensor



ZAI-SS-GS

Type	Smart Gas Sensor
Input Voltage	100-240VAC 50/60Hz
Detection Gas	Marsh - Coal - Liquefied Methane - Natural
Detection Speed	0.08Second
Power Consumption	3W
Alarm Volume	70db/1mt.

Smart Gas Sensor



ZAI-SS-GS-MINI

Type	Smart Gas Sensor
Input Voltage	100-240VAC 50/60Hz
Detection Gas	Bio - CH4 - Liquefied - Natural
Detection Speed	0.08Second
Power Consumption	1,5W
Alarm Volume	70db/1mt.

